


# White LED Straight Cove Lighting



## Product Description

The White LED Straight Cove Lights are designed for multiple applications with a non-ferrous assembly which can be mounted in recessed applications in a healthcare facility. Consult factory for custom shapes. All drive circuitry employs linear regulation and no pulse width modulation (PWM\*).

Performance Summary
Input Power: 23 watts
Limited Warranty: 3 years
Lifetime: Designed to last 50,000 hours
Dimming: Linear



Mechanical	Minimum	Typical	Maximum	Units
Package	-	LED Strip	-	-
Electrical Connection	-	Junction Box	-	-
Dimensions	-	6.75W x 6 3/8D	-	inches
Fixture Weight	-	23	-	lbs

Electrical (per Section)	Minimum	Typical	Maximum	Units
Input Voltage	-	12	-	Vdc
Input Current	-	1.9	-	A
Input Power	-	23	-	W
Heat	-	78	-	BTU/h

Compliance	Minimum	Typical	Maximum	Units
IP	25	-	-	Dry Location
Regulatory	-	Listed	-	UL 2108 CSA 22.2#250.0
RoHS	-	Pending	-	2011/65/EU

Environmental	Minimum	Typical	Maximum	Units
Storage Temperature	-40	25	85	C
Operating Temperature	-20	25	35	C
Humidity	5	-	95	%
Lifespan	50000	-	-	Hours
Warranty	3	-	-	Years

Installation Notes
*PWM is known to cause image artifacts, audible noise and light flicker

1-07-000088




PDC Specification Submittal	
Job Name:	
Job Number:	
Model Numbers:	Fixture Type:



Photometric Data

Photometric				
	Minimum	Typical	Maximum	Units
Luminous Flux (per section)	850	-	-	lm
CCT	-	3100	-	k
CRI	72.9	-	-	
Chromaticity (u')	-	0.244	-	
Chromaticity (v')	-	0.519	-	
Efficacy	-	73	-	lm/W

Spectral Data Over Visible Wavelength



Mechanical Diagram

