VERSAVIDEO[®] 65" Wall Mounted Video Display MRI Compatible



Product Description

VERSAVIDEO[®] Video Displays bring the healing quality of nature or a favorite movie to patients with the tap of a finger. The Video Displays are engineered specifically for MRI applications and feature PDC's original Nature Videography, DVD integration or customer supplied content. Original 4K Nature Theme videography was developed to alleviate MRI anxiety and improve patient satisfaction. Additional compatible music or patient audio system are also an option. All components are non-ferrous. Certified to meet MRI vendor EMI requirements. MRI applications require EMI free emissions for specific frequency bands. All outputs are linear DC and no pulse width modulation (PWM*).

Features and Benefits

MRI-Safe Video Display, RF Shielded and 4K resolution Engineered specifically for MRI environments Portrait, landscape and multiple-display configurations available Optional Touch Control System Optional Theme lighting and Theme audio integration Option for patient preview and Theme selection in a waiting area

Electrical				
	Minimum	Typical	Maximum	Units
Input Voltage	-	42	-	VDC
Input Power	-	120	-	W
Input Current	-	3	-	ADC
Heat	-	409	-	BTU/h
Refresh Rate	-	60	-	Hz


Inputs		
	Connection	Function
Power	42 VDC Wires	DC+
Power	42 VDC Wires	DC-
Fiber ST (2)	Fiber	Video

Compliance				
	Minimum	Typical	Maximum	Units
				UL 62368-1
				CSA C22.2 #62368-1
Regulatory Safety	-	Listed	-	IEC 62368-1
				IEC 60065
				IEC 60950-1
CE	-	Pending	-	
RoHS	-	Pending	-	2011/65/EU

Environmental				
	Minimum	Typical	Maximum	Units
Storage	-40	25	60	°c
Operating Temperature	0	25	40	°c
Humidity	20	-	80	%
Warranty	-	1	-	Years

Installation Notes

A RF Filter and PDC VERSAVIDEO[®] Controller are required for proper operation in the MRI scan room. *PWM is known to cause image artifacts, audible noise and light flicker





PDC Specification Submittal

Job Name:	
Job Number:	
Model Numbers:	Fixture Type:



Dimensions				
	Width	Height	Depth	Units
Monitor	64.7	42.5	3.6	inches
Monitor Resolution	3840	2160	-	pixels
Mechanical				
	Minimum	Typical	Maximum	Units
Enclosure	-	5052-H32 AL / Tempered Glass	-	-
Construction	-	Welded	-	-
Product Weight	-	-	200	lbs
Viewing Angle	-	178	-	-

Mechanical Diagram

